Declaration of Performance (DoP)

MS Polimer



PV/LE/DoP-Nr. 340-001

1. Identification of product type: MS Polimer

2. Identification no.:3. Designated use:4. See product packaging for batch code5. 1-component hybrid polymer sealant,

Neutral curing.

Sealant for application in facade: Type F-INT

4. Manufacturer: TechnicqII Sp. z o. o.

Ul. Armii Krajowej 34

32-540 Trzebinia

Poland

5. Authorized representative:

6. System for evaluating reliability of

performance:

3 plus 3

7. Harmonized standard: EN 15651-1: 2012-12

8. Notified body: IFT Rosenheim (NB-nr. 0757)

9. Important characteristics:

Important characteristic	Performance	Harmonized technical specification
Fire behaviour	Class E	EN 15651-1: 2012-12 Conditioning: Method B Beton with Primer
Release of hazardous chemicals to health and/or the environment	Evaluated	
Stability under load	≤ 3mm	
Volume loss	≤ 45%	
Tensile properties at 23°C	≥ 25%	
Tear resistance	NF	
Durability	NF	NF = non failure / passed

10. The performance of the product as per number 1 and number 2 is conform to the performance as set out under number 9.

This declaration of performance is issued under the responsibility of the manufacturer identified in point 4.

Signed on behalf of the Producer: Monika Stańczyk in Trzebinia on 10-11-2023

Versie 20190730





